



## DECLARATION OF PERFORMANCE

No. FLORIM 001

- Unique identification code of the product type  
Type, batch or serial number or any other element allowing identification of the product  
**Dry-pressed ceramic tiles, with water absorption  $E_b \leq 0,5 \%$**
- Intended use(s)  
**For internal and external walls and floorings**
- Name or registered trade mark, and contact address of the manufacturer  
**FLORIM CERAMICHE S.p.A.,  
Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia**
- System(s) of assessment and verification of constancy of performance (AVCP)  
**System 4**
- Name and identification number of notified laboratory, if relevant – **Not applicable**  
Task(s) carried out  
AVCP system  
Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 <sub>FL</sub> /A1	Based on the decision 96/603/CE and its changes  <b>EN 14411:2012</b>
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1300 N	
Slipperiness	See table attached	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	NPD	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	


The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Bruni Donato – Amministratore Delegato

.....  
Name and function

Fiorano Modenese, 25/06/2013

.....  
Place and date of issue

  
.....  
Signature



**Allegato alla Dichiarazione di Prestazione**  
**Attachment to Declaration of Performance**  
**Annexe à la déclaration de performance**  
**Anhang der Leistungserklärung**  
**Anexo a la Declaración de Performance**  
**Załącznik do deklaracji właściwości użytkowych**  
**A Teljesítmény Nyilatkozat kiegészítő táblázata**  
**Bijlage bij de prestatieverklaring**  
**Navezanost na izjave o lastnostih**  
**Aneks Izjave o svojstvima**  
**No. FLORIM 001**

**Tabella - Scivolosità (dove richiesto dalla legislazione)**  
**Table - Slipperiness (where required by regulation)**  
**Table - Glissement (si requis par la loi)**  
**Tabelle - Rutsicherheit (wo erforderlich durch die Gesetzgebung)**  
**Tabla - Deslizamiento (donde sea requerido por ley)**  
**Tabela - Poslizgowosc (gdzie wymagane przez prawo)**  
**Táblázat - Csúszásmentesség (ahol jogszabály szerint szükséges)**  
**Tabel - Antislipwaarde (indien door de wetgever vereist)**  
**Tabela - Drsnosti (samo ko tako zahteva državna zakonodaja)**  
**Tablica - Otpornost na klizanje (gdje je ta zakonski zatraženo)**  
**Rev. 14 del/of/de/vom/de/a 01.12.2020**

**Marchio / Brand / Marque / Marke / Marca / Znak handlowy / Márka / Merk / Znamka / Trgovačka marka**

## CASA DOLCE CASA


Serie / Series / Kolekcja / Serija	CENTS 16165:2012 Annex B $\alpha_{SHOD}$	BCRA DM 236/1989 (ITA)	DIN 51130 (DE)	Documento basico SU 3/2006 (ESP)
ARTWORK glossy	N.P.D.	>0,4	N.P.D.	N.P.D.
ARTWORK matte	$\alpha$ da 6° a 10°	N.P.D.	R9	N.P.D.
ARTWORK R+PTV	$\alpha$ da 11° a 19°	>0,4	R10	N.P.D.
FLAGSTONE 2.0 glossy	N.P.D.	>0,4	N.P.D.	N.P.D.
FLAGSTONE 2.0 matte	$\alpha$ da 11° a 19°	N.P.D.	R10	N.P.D.
FLAGSTONE 2.0 strutturato	$\alpha$ da 20° a 27°	>0,4	R11	N.P.D.
ICON OUTDOOR	$\alpha$ da 20° a 27°	>0,4	R11	N.P.D.
MOTION	$\alpha$ da 6° a 10°	N.P.D.	R9	N.P.D.
MOTION strutturato	$\alpha$ da 20° a 27°	>0,4	R11	Classe 3
NEUTRA 6.0 tinte unite	N.P.D.	N.P.D.	N.P.D.	N.P.D.
NEUTRA 6.0 tinte unite grip	$\alpha$ da 20° a 27°	>0,4	R11	N.P.D.
ONYX & MORE GLOSSY	N.P.D.	>0,4	N.P.D.	N.P.D.
ONYX & MORE SATIN	N.P.D.	>0,4	N.P.D.	N.P.D.
ONYX & MORE STRUTTURATO	$\alpha$ da 11° a 19°	>0,4	R10	Classe 1
PIETRE 3 naturale	$\alpha$ da 11° a 19°	>0,4	R10	N.P.D.
PIETRE 3 strutturato	$\alpha$ da 20° a 27°	>0,4	R11	N.P.D.
PIETRE 3 strutturato 20 mm	$\alpha$ da 20° a 27°	>0,4	R11	N.P.D.
SENSI Dust Fossil matte	$\alpha$ da 6° a 10°	>0,4	R9	N.P.D.
SENSI Fossil R+PTV	$\alpha$ da 11° a 19°	>0,4	R10	Classe 2
SENSI Lithos matte	$\alpha$ da 11° a 19°	>0,4	R10	N.P.D.
SENSI Sand matte	$\alpha$ da 20° a 27°	>0,4	R11	N.P.D.
STONES & MORE 2.0 matte (stone burl white-)	$\alpha$ da 11° a 19°	>0,4	R10	N.P.D.
STONES & MORE 2.0 smooth	$\alpha$ da 6° a 10°	>0,4	R9	N.P.D.
STONES & More 2.0 glossy	N.P.D.	>0,4	N.P.D.	N.P.D.
STONES & MORE 2.0 matte (Stone Marfil-Ston	$\alpha$ da 6° a 10°	>0,4	R9	N.P.D.
STUDIOS OF CASAMOOD grip	$\alpha$ da 20° a 27°	>0,4	R11	N.P.D.
STUDIOS OF CASAMOOD grip 20 mm	$\alpha$ da 20° a 27°	>0,4	R11	N.P.D.
STUDIOS OF CASAMOOD matte	$\alpha$ da 11° a 19°	N.P.D.	R10	N.P.D.



URBAN STYLE	$\alpha$ da 11° a 19°	>0,4	R10	N.P.D.
URBAN STYLE STRUTTURATO	$\alpha$ da 20° a 27°	>0,4	R11	N.P.D.
URBAN STYLE STRUTTURATO 20 MM	$\alpha$ da 20° a 27°	>0,4	R11	N.P.D.
WOODEN TILE WALNUT naturale	$\alpha$ da 6° a 10°	>0,4	R9	Classe 1
WOODEN TILE naturale	$\alpha$ da 11° a 19°	>0,4	R10	N.P.D.
WOODEN TILE strutturato	$\alpha$ da 20° a 27°	>0,4	R11	Classe 2

# CE MARKING

Fine porcelain stoneware  
Glazed porcelain stoneware  
Coloured body porcelain stoneware

	
<b>FLORIM CERAMICHE S.p.A., Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia</b>	
05 FLORIM 001	
<b>EN 14411:2012</b> Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$ , for internal and external walls and floorings	
<b>Reaction to fire</b>	A1 <sub>FL</sub> /A1
<b>Release of dangerous substances, for:</b>	
- Cadmium	NPD
- Lead	NPD
<b>Breaking strength</b>	> 1300 N
<b>Slipperiness, as:</b>	See table attached
<b>Tactility</b>	NPD
<b>Bond strength/adhesion, for:</b>	
Cementitious adhesive, type C2	NPD
<b>Thermal shock resistance</b>	Pass
<b>Durability, for:</b>	
- internal use:	Pass
- external use: freeze-thaw resistance	Pass