

DECLARATION OF CONFORMITY

No. **FLORIM 001** UKCA

(EN) - Rev. 0

1. Unique identification code of the product type
Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$
2. Intended use(s)
For internal and external walls and floorings
3. Name or registered trade mark, and contact address of the manufacturer
**FLORIM CERAMICHE S.p.A. SB,
Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia**
4. System(s) of assessment and verification of constancy of performance (AVCP)
System 4
5. Name and identification number of notified laboratory, if relevant – **Not applicable**
6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1_{FL}/A1	Based on the decision 96/603/CE and its changes BS EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1300 N	
Slipperiness	See table attached	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	NPD	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of conformity is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Bruni Donato – Amministratore Delegato

.....
Name and function

Fiorano Modenese, 01/09/2021

.....
Place and date of issue


.....
Signature



Allegato alla Dichiarazione di Prestazione
Attachment to Declaration of Performance
Annexe à la déclaration de performance
Anhang der Leistungserklärung
Anexo a la Declaración de Performance
Załącznik do deklaracji właściwości użytkowych
A Teljesítmény Nyilatkozat kiegészítő táblázata
Bijlage bij de prestatieverklaring
Navezanost na izjave o lastnostih
Aneks Izjave o svojstvima
No. FLORIM 001

Tabella - Scivolosità (dove richiesto dalla legislazione)
Table - Slipperiness (where required by regulation)
Table - Glissement (si requis par la loi)
Tabelle - Rutschsicherheit (wo erforderlich durch die Gesetzgebung)
Tabla - Deslizamiento (donde sea requerido por ley)
Tabela - Poslizgowosc (gdzie wymagane przez prawo)
Táblázat - Csúszásmentesség (ahol jogsabály szerint szükséges)
Tabel - Antislipwaarde (indien door de wetgever vereist)
Tabela - Drsnosti (samo ko tako zahteva državna zakonodaja)
Tablica - Otpornost na klizanje (gdje je ta zakonski zatraženo)
Rev. 13 del/of/de/vom/de/a 19.10.2021

Marchio / Brand / Marque / Marke / Marca / Znak handlowy / Márka / Merk / Znamka / Trgovačka marka

CERIM


Serie / Series / Kolekcja / Serija	CENT/TS 16'165:2012 Annex B α_{SHOD}	BCRA DM 236/1989 (ITA)	DIN 51130 (DE)	Documento basico SU 3/2006 (ESP)
ANTIQUE MARBLE lucido	N.P.D.	>0,4	N.P.D.	N.P.D.
ANTIQUE MARBLE matte	N.P.D.	>0,4	N.P.D.	N.P.D.
ANTIQUE MARBLE STRUTTURATO	N.P.D.	N.P.D.	R10	N.P.D.
ARTIFACT OF CERIM grip	N.P.D.	>0,4	R12	N.P.D.
ARTIFACT OF CERIM naturale	N.P.D.	>0,4	R10	N.P.D.
DETAILS WOOD OF CERIM grip 20 mm	N.P.D.	>0,4	R11	N.P.D.
DETAILS WOOD OF CERIM matte	N.P.D.	>0,4	R9	N.P.D.
ELEMENTAL STONE OF CERIM grip	N.P.D.	>0,4	R11	N.P.D.
ELEMENTAL STONE OF CERIM lucido	N.P.D.	N.P.D.	N.P.D.	N.P.D.
ELEMENTAL STONE OF CERIM matte	N.P.D.	>0,4	R10	N.P.D.
EXALT OF CERIM lucido	N.P.D.	>0,4	N.P.D.	N.P.D.
EXALT OF CERIM naturale	N.P.D.	>0,4	N.P.D.	N.P.D.
HI WOOD OF CERIM lucido	N.P.D.	>0,4	N.P.D.	N.P.D.
HI WOOD OF CERIM naturale	N.P.D.	>0,4	R10	N.P.D.
LE VENEZIANE lucido	N.P.D.	N.P.D.	N.P.D.	N.P.D.
LE VENEZIANE naturale	N.P.D.	>0,4	R9	N.P.D.
LE VENEZIANE R+PTV	N.P.D.	>0,4	R10	N.P.D.
MAPS OF CERIM bocciardato	N.P.D.	>0,4	R11	N.P.D.
MAPS OF CERIM bocciardato 2 cm	N.P.D.	>0,4	R11	N.P.D.
MAPS OF CERIM matte	N.P.D.	>0,4	R10	N.P.D.
MATCH UP comfort	N.P.D.	>0,4	R10	N.P.D.
MATCH UP grip	N.P.D.	>0,4	R11	N.P.D.
MATCH UP grip 20 mm	N.P.D.	>0,4	R11	N.P.D.
MATERIAL STONES OF CERIM bocciardato 20 r	N.P.D.	>0,4	R11	N.P.D.
MATERIAL STONES OF CERIM grip	N.P.D.	>0,4	R11	N.P.D.
MATERIAL STONES OF CERIM matte	N.P.D.	N.P.D.	R9	N.P.D.
NATURAL STONE OF CERIM bocciardato 20 r	N.P.D.	>0,4	R11	N.P.D.



NATURAL STONE OF CERIM grip	N.P.D.	>0,4	R11	N.P.D.
NATURAL STONE OF CERIM matte	N.P.D.	>0,4	R10	Classe 2
ONIX OF CERIM lucido	N.P.D.	>0,4	N.P.D.	N.P.D.
ONIX OF CERIM matte	N.P.D.	>0,4	N.P.D.	N.P.D.
ROCK SALT OF CERIM bocciardato	N.P.D.	>0,4	R11	N.P.D.
ROCK SALT OF CERIM lucido	N.P.D.	>0,4	N.P.D.	N.P.D.
ROCK SALT OF CERIM matte	N.P.D.	>0,4	R10	N.P.D.
TIMELESS grip	N.P.D.	>0,4	R11	N.P.D.
TIMELESS lucido	N.P.D.	>0,4	N.P.D.	N.P.D.
TIMELESS matte	N.P.D.	>0,4	R9	N.P.D.

CE MARKING

Fine porcelain stoneware
Glazed porcelain stoneware
Coloured body porcelain stoneware

	
FLORIM CERAMICHE S.p.A. SB, Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia	
05 FLORIM 001	
EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$, for internal and external walls and floorings	
Reaction to fire	A1 _{FL} /A1
Release of dangerous substances, for:	
- Cadmium	NPD
- Lead	NPD
Breaking strength	> 1300 N
Slipperiness, as:	See table attached
Tactility	NPD
Bond strength/adhesion, for:	
Cementitious adhesive, type C2	NPD
Thermal shock resistance	Pass
Durability, for:	
- internal use:	Pass
- external use: freeze-thaw resistance	Pass
https://www.florim.com/en/complete-ce-marking/	