

DECLARATION OF PERFORMANCE

No. FLORIM 003

1. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$
2. Intended use(s)
For internal and external walls and floorings
3. Name or registered trade mark, and contact address of the manufacturer
**FLORIM CERAMICHE S.p.A.,
Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia**
4. System(s) of assessment and verification of constancy of performance (AVCP)
System 4
5. Name and identification number of notified laboratory, if relevant – **Not applicable**
Task(s) carried out
AVCP system
Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1_{FL}/A1	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 700 N	
Slipperiness	See table attached	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	NPD	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Bruni Donato – Amministratore Delegato

.....
Name and function

Fiorano Modenese, 25/06/2013

.....
Place and date of issue



.....
Signature



Allegato alla Dichiarazione di Prestazione
Attachment to Declaration of Performance
Annexe à la déclaration de performance
Anhang der Leistungserklärung
Anexo a la Declaración de Performance
Załącznik do deklaracji właściwości użytkowych
A Teljesítmény Nyilatkozat kiegészítő táblázata
Bijlage bij de prestatieverklaring
Navezanost na izjave o lastnostih
Aneks Izjave o svojstvima
No. FLORIM 003

Tabella - Scivolosità (dove richiesto dalla legislazione)
Table - Slipperiness (where required by regulation)
Table - Glissement (si requis par la loi)
Tabelle - Rutsicherheit (wo erforderlich durch die Gesetzgebung)
Tabla - Deslizamiento (donde sea requerido por ley)
Tabela - Poslizgowosc (gdzie wymagane przez prawo)
Táblázat - Csúszásmentesség (ahol jogszabály szerint szükséges)
Tabel - Antislipwaarde (indien door de wetgever vereist)
Tabela - Drsnosti (samo ko tako zahteva državna zakonodaja)
Tablica - Otpornost na klizanje (gdje je ta zakonski zatraženo)
Rev. 7 del/of/de/vom/de/a 19.12.2018

Marchio / Brand / Marque / Marke / Marca / Znak handlowy / Márka / Merk / Znamka / Trgovačka marka

REX


Serie / Series / Kolekcja / Serija	CENTS 16165:2012 Annex B α_{SHOD}	BCRA DM 236/1989 (ITA)	DIN 51130 (DE)	Documento basico SU 3/2006 (ESP)
ALABASTRI DI REX Magnum glossy	N.P.D.	N.P.D.	N.P.D.	N.P.D.
ARDOISE Magnum matte	α da 6° a 10°	> 0,4	R9	N.P.D.
ETOLIE DE REX magnum glossy	N.P.D.	N.P.D.	N.P.D.	N.P.D.
I BIANCHI DI REX Magnum glossy	N.P.D.	N.P.D.	N.P.D.	N.P.D.
I CLASSICI DECO' WOOD Magnum	α da 6° a 10°	> 0,4	R9	N.P.D.
I CLASSICI DI REX Magnum glossy	N.P.D.	N.P.D.	N.P.D.	N.P.D.
I CLASSICI DI REX Magnum matte/soft	N.P.D.	N.P.D.	N.P.D.	N.P.D.
I MARMI DI REX Magnum glossy	N.P.D.	N.P.D.	N.P.D.	N.P.D.
I TRAVERTINI DI REX Magnum glossy	N.P.D.	N.P.D.	N.P.D.	N.P.D.
I TRAVERTINI DI REX Magnum matte	N.P.D.	N.P.D.	N.P.D.	N.P.D.
LA ROCHE Magnum smooth	N.P.D.	> 0,4	N.P.D.	N.P.D.
MATIERES DI REX Magnum matte	α da 6° a 10°	N.P.D.	R9	N.P.D.
MATIERES DI REX Magnum R+PTV	α da 11° a 19°	>0,4	R10	N.P.D.
PIETRA DEL NORD Magnum soft	N.P.D.	N.P.D.	N.P.D.	N.P.D.
PREXIOUS Magnum glossy	N.P.D.	> 0,4	N.P.D.	N.P.D.
PREXIOUS Magnum matte	N.P.D.	N.P.D.	N.P.D.	N.P.D.
SELECTION OAK Magnum naturale	α da 11° a 19°	> 0,4	R10	N.P.D.



FLORIM CERAMICHE S.p.A. a socio unico
VIA CANALETTO 24 / 41042 FIORANO MODENESE (MO) ITALY
T. +39 0536 840111 / F. +39 0536 840322
www.florim.com

CE MARKING

Fine porcelain stoneware SLIM/4
Coloured body porcelain stoneware SLIM/4
Fine porcelain stoneware MAGNUM

	
FLORIM CERAMICHE S.p.A., Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia	
09 FLORIM 003	
EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$, for internal and external walls and floorings	
Reaction to fire	A1 _{FL} /A1
Release of dangerous substances, for:	
- Cadmium	NPD
- Lead	NPD
Breaking strength	> 700 N
Slipperiness, as:	See table attached
Tactility	NPD
Bond strength/adhesion, for:	
Cementitious adhesive, type C2	NPD
Thermal shock resistance	Pass
Durability, for:	
- internal use:	Pass
- external use: freeze-thaw resistance	Pass