

## DECLARATION OF PERFORMANCE

No. FLORIM 003

1. Unique identification code of the product type  
 Type, batch or serial number or any other element allowing identification of the product  
**Dry-pressed ceramic tiles, with water absorption  $E_b \leq 0,5 \%$**
2. Intended use(s)  
**For internal and external walls and floorings**
3. Name or registered trade mark, and contact address of the manufacturer  
**FLORIM CERAMICHE S.p.A.,  
 Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia**
4. System(s) of assessment and verification of constancy of performance (AVCP)  
**System 4**
5. Name and identification number of notified laboratory, if relevant – **Not applicable**  
 Task(s) carried out  
 AVCP system  
 Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
<b>Reaction to fire</b>	<b>A1<sub>FL</sub>/A1</b>	<b>Based on the decision 96/603/CE and its changes</b>             <b>EN 14411:2012</b>
<b>Release of dangerous substance, for:</b>		
- Cadmium	NPD	
- Lead	NPD	
<b>Breaking strength</b>	<b>&gt; 700 N</b>	
<b>Slipperiness</b>	See table attached	
<b>Tactility</b>	NPD	
<b>Bond strength/adhesion, for:</b>		
Cementitious adhesive, type C2	NPD	
<b>Thermal shock resistance</b>	<b>Pass</b>	
<b>Durability for:</b>		
- internal use:	<b>Pass</b>	
- external use: freeze-thaw resistance	<b>Pass</b>	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Bruni Donato – Amministratore Delegato

Name and function

Fiorano Modenese, 25/06/2013

Place and date of issue

Signature



Allegato alla Dichiarazione di Prestazione  
Attachment to Declaration of Performance  
Annexe à la déclaration de performance  
Anhang der Leistungserklärung  
Anexo a la Declaración de Performance  
Załącznik do deklaracji właściwości użytkowych  
A Teljesítmény Nyilatkozat kiegészítő táblázata  
Bijlage bij de prestatieverklaring  
Navezanost na izjave o lastnostih  
Aneks Izjave o svojstvima  
No. FLORIM 003

Tabella - Scivolosità (dove richiesto dalla legislazione)  
Table - Slipperiness (where required by regulation)  
Table - Glissement (si requis par la loi)  
Tabelle - Rutsicherheit (wo erforderlich durch die Gesetzgebung)  
Tabla - Deslizamiento (donde sea requerido por ley)  
Tabela - Poslizgowosc (gdzie wymagane przez prawo)  
Táblázat - Csúszásmentesség (ahol jogszabály szerint szükséges)  
Tabel - Antislipwaarde (indien door de wetgever vereist)  
Tabela - Drsnosti (samo ko tako zahteva državna zakonodaja)  
Tablica - Otpornost na klizanje (gdje je ta zakonski zatraženo)  
Rev. 7 del/of/de/vom/de/a 19.12.2018

Marchio / Brand / Marque / Marke / Marca / Znak handlowy / Márka / Merk / Znamka / Trgovačka marka

REX


Serie / Series / Kolekcja / Serija	CENTS 16165:2012 Annex B $\alpha_{SHOD}$	BCRA DM 236/1989 (ITA)	DIN 51130 (DE)	Documento basico SU 3/2006 (ESP)
ALABASTRI DI REX Magnum glossy	N.P.D.	N.P.D.	N.P.D.	N.P.D.
ARDOISE Magnum matte	$\alpha$ da 6° a 10°	>0,4	R9	N.P.D.
ETOILE DE REX magnum glossy	N.P.D.	N.P.D.	N.P.D.	N.P.D.
I BIANCHI DI REX Magnum glossy	N.P.D.	N.P.D.	N.P.D.	N.P.D.
I CLASSICI DECO' WOOD Magnum	$\alpha$ da 6° a 10°	>0,4	R9	N.P.D.
I CLASSICI DI REX Magnum glossy	N.P.D.	N.P.D.	N.P.D.	N.P.D.
I CLASSICI DI REX Magnum matte/soft	N.P.D.	N.P.D.	N.P.D.	N.P.D.
I MARMI DI REX Magnum glossy	N.P.D.	N.P.D.	N.P.D.	N.P.D.
I TRAVERTINI DI REX Magnum glossy	N.P.D.	N.P.D.	N.P.D.	N.P.D.
I TRAVERTINI DI REX Magnum matte	N.P.D.	N.P.D.	N.P.D.	N.P.D.
LA ROCHE Magnum smooth	N.P.D.	>0,4	N.P.D.	N.P.D.
MATIERES DI REX Magnum matte	$\alpha$ da 6° a 10°	N.P.D.	R9	N.P.D.
MATIERES DI REX Magnum R+PTV	$\alpha$ da 11° a 19°	>0,4	R10	N.P.D.
PIETRA DEL NORD Magnum soft	N.P.D.	N.P.D.	N.P.D.	N.P.D.
PREXIOUS Magnum glossy	N.P.D.	>0,4	N.P.D.	N.P.D.
PREXIOUS Magnum matte	N.P.D.	N.P.D.	N.P.D.	N.P.D.
SELECTION OAK Magnum naturale	$\alpha$ da 11° a 19°	>0,4	R10	N.P.D.



FLORIM CERAMICHE S.p.A. a socio unico  
VIA CANALETTO 24 / 41042 FIORANO MODENESE (MO) ITALY  
T. +39 0536 840111 / F. +39 0536 840322  
[www.florim.com](http://www.florim.com)

# CE MARKING

Fine porcelain stoneware SLIM/4  
Coloured body porcelain stoneware SLIM/4  
Fine porcelain stoneware MAGNUM

	
<b>FLORIM CERAMICHE S.p.A.,</b> <b>Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia</b>	
09 FLORIM 003	
<b>EN 14411:2012</b> Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$ , for internal and external walls and floorings	
<b>Reaction to fire</b>	A1 <sub>FL</sub> /A1
<b>Release of dangerous substances, for:</b>	
- Cadmium	NPD
- Lead	NPD
<b>Breaking strength</b>	> 700 N
<b>Slipperiness, as:</b>	See table attached
<b>Tactility</b>	NPD
<b>Bond strength/adhesion, for:</b>	
Cementitious adhesive, type C2	NPD
<b>Thermal shock resistance</b>	Pass
<b>Durability, for:</b>	
- internal use:	Pass
- external use: freeze-thaw resistance	Pass