



## DECLARATION OF PERFORMANCE

No. FLORIM 001

1. Unique identification code of the product type  
**Dry-pressed ceramic tiles, with water absorption  $E_b \leq 0,5 \%$**
2. Intended use(s)  
**For internal and external walls and floorings**
3. Name or registered trade mark, and contact address of the manufacturer  
**FLORIM CERAMICHE S.p.A. SB,  
Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia**
4. System(s) of assessment and verification of constancy of performance (AVCP)  
**System 4**
5. Name and identification number of notified laboratory, if relevant – **Not applicable**  
Task(s) carried out  
AVCP system  
Document issued and date of issue
6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 <sub>FL</sub> /A1	Based on the decision 96/603/CE and its changes
Release of dangerous substance, for:		EN 14411:2012
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1300 N	
Slipperiness	See table attached	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	NPD	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued in accordance with regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3. This declaration is available on the website <https://www.florim.com/en/declarations-of-performance-ce/>. Signed for and on behalf of the manufacturer by:

Bruni Donato – Amministratore Delegato

.....  
Name and function

Fiorano Modenese, 01/03/2021

.....  
Place and date of issue

  
.....  
Signature



Allegato alla Dichiarazione di Prestazione  
Attachment to Declaration of Performance  
Annexe à la déclaration de performance  
Anhang der Leistungserklärung  
Anexo a la Declaración de Performance  
Załącznik do deklaracji właściwości użytkowych  
A Teljesítmény Nyilatkozat kiegészítő táblázata  
Bijlage bij de prestatieverklaring  
Navezanost na izjave o lastnostih  
Aneks Izjave o svojstvima  
No. FLORIM 001

Tabella - Scivolosità (dove richiesto dalla legislazione)  
Table - Slipperiness (where required by regulation)  
Table - Glissement (si requis par la loi)  
Tabelle - Rutschsicherheit (wo erforderlich durch die Gesetzgebung)  
Tabla - Deslizamiento (donde sea requerido por ley)  
Tabela - Poslizgowosc (gdzie wymagane przez prawo)  
Táblázat - Csúszásmentesség (ahol jogsabály szerint szükséges)  
Tabel - Antislipwaarde (indien door de wetgever vereist)  
Tabela - Drsnosti (samo ko tako zahteva državna zakonodaja)  
Tablica - Otpornost na klizanje (gdje je ta zakonski zatraženo)  
Rev. 13 del/of/de/vom/de/a 29.04.2021

Marchio / Brand / Marque / Marke / Marca / Znak handlowy / Márka / Merk / Znamka / Trgovačka marka

REX


Serie / Series / Kolekcja / Serija	CEN/TS 16165:2012 Annex B $\alpha_{SHOD}$	BCRA DM 236/1989 (ITA)	DIN 51130 (DE)	Documento basico SU 3/2006 (ESP)
ALABASTRI DI REX shiny	N.P.D.	>0,4	N.P.D.	N.P.D.
ARDOISE grip	N.P.D.	>0,4	R11	Classe 2
ARDOISE matte	N.P.D.	>0,4	R10	Classe 1
ESPRIT DE REX matte	N.P.D.	N.P.D.	R9	N.P.D.
ESPRIT DE REX strutturato	N.P.D.	>0,4	R11	N.P.D.
ETOILE DE REX glossy	N.P.D.	N.P.D.	N.P.D.	N.P.D.
ETOILE DE REX matte	N.P.D.	N.P.D.	N.P.D.	N.P.D.
I CLASSICI DI REX glossy	N.P.D.	>0,4	N.P.D.	N.P.D.
I CLASSICI DI REX matte/soft	N.P.D.	>0,4	N.P.D.	N.P.D.
I MARMI DI REX matte	N.P.D.	>0,4	R9	N.P.D.
I MARMI DI REX shiny	N.P.D.	>0,4	N.P.D.	N.P.D.
LA ROCHE smooth	N.P.D.	>0,4	R9	N.P.D.
LA ROCHE strutturato	N.P.D.	>0,4	R11	Classe 2
LA ROCHE strutturato 20 mm	N.P.D.	>0,4	R11	Classe 2
LES BIJOUX DE REX glossy	N.P.D.	>0,4	N.P.D.	N.P.D.
LES BIJOUX DE REX matte	N.P.D.	N.P.D.	N.P.D.	N.P.D.
LES ORIGINES DE REX glossy	N.P.D.	N.P.D.	N.P.D.	N.P.D.
LES ORIGINES DE REX naturale	N.P.D.	N.P.D.	N.P.D.	N.P.D.
MATIERES DI REX matte	N.P.D.	>0,4	R10	N.P.D.
MATIERES DI REX strutturato 20 mm	N.P.D.	>0,4	R11	N.P.D.
PLANCHES DI REX naturale	N.P.D.	>0,4	R10	N.P.D.
PLANCHES DI REX strutturato	N.P.D.	>0,4	R11	N.P.D.
PREXIOUS glossy	N.P.D.	>0,4	N.P.D.	N.P.D.
PREXIOUS matte	N.P.D.	N.P.D.	N.P.D.	N.P.D.
REVES DE REX glossy	N.P.D.	N.P.D.	N.P.D.	N.P.D.
REVES DE REX naturale	N.P.D.	N.P.D.	N.P.D.	N.P.D.
SELECTION OAK naturale	N.P.D.	>0,4	R9	N.P.D.



SELECTION OAK strutturato	N.P.D.	>0,4	R11	N.P.D.
SELECTION OAK strutturato 20 mm	N.P.D.	>0,4	R11	N.P.D.

# CE MARKING

Fine porcelain stoneware  
Glazed porcelain stoneware  
Coloured body porcelain stoneware

	
<b>FLORIM CERAMICHE S.p.A. SB, Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia</b>	
05 FLORIM 001	
<b>EN 14411:2012</b> Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$ , for internal and external walls and floorings	
<b>Reaction to fire</b>	A1 <sub>FL</sub> /A1
<b>Release of dangerous substances, for:</b>	
- Cadmium	NPD
- Lead	NPD
<b>Breaking strength</b>	> 1300 N
<b>Slipperiness, as:</b>	See table attached
<b>Tactility</b>	NPD
<b>Bond strength/adhesion, for:</b>	
Cementitious adhesive, type C2	NPD
<b>Thermal shock resistance</b>	Pass
<b>Durability, for:</b>	
- internal use:	Pass
- external use: freeze-thaw resistance	Pass
<a href="https://www.florim.com/en/complete-ce-marking/">https://www.florim.com/en/complete-ce-marking/</a>	