





Allegato alla Dichiarazione di Prestazione  
Attachment to Declaration of Performance  
Annexe à la déclaration de performance  
Anhang der Leistungserklärung  
Anexo a la Declaración de Performance  
Załącznik do deklaracji właściwości użytkowych  
A Teljesítmény Nyilatkozat kiegészítő táblázata  
Bijlage bij de prestatieverklaring  
Navezanost na izjave o lastnostih  
Aneks Izjave o svojstvima  
No. FLORIM 003

Tabella - Scivolosità (dove richiesto dalla legislazione)  
Table - Slipperiness (where required by regulation)  
Table - Glissement (si requis par la loi)  
Tabelle - Rutsicherheit (wo erforderlich durch die Gesetzgebung)  
Tabla - Deslizamiento (donde sea requerido por ley)  
Tabela - Poslizgowosc (gdzie wymagane przez prawo)  
Táblázat - Csúszásmentesség (ahol jogszabály szerint szükséges)  
Tabel - Antislipwaarde (indien door de wetgever vereist)  
Tabela - Drsnosti (samo ko tako zahteva državna zakonodaja)  
Tablica - Otpornost na klizanje (gdje je ta zakonski zatraženo)  
Rev. 1 del/of/de/vom/de/a 17.12.2019

Marchio / Brand / Marque / Marke / Marca / Znak handlowy / Márka / Merk / Znamka / Trgovačka marka

## FLORIMSTONE


| Serie / Series / Kolekcja / Serija | CEN/TS<br>16165:2012<br>Annex B $\alpha_{SHOD}$ | BCRA DM<br>236/1989<br>(ITA) | DIN 51130<br>(DE) | Documento<br>basico SU<br>3/2006 (ESP) |
|------------------------------------|---|------------------------------|-------------------|--|
| CEMENT matt 6 mm                   | N.P.D.  | >0,4                         | N.P.D.            | N.P.D.                                 |
| CEMENT velvet 6 mm                 | N.P.D.  | >0,4                         | N.P.D.            | N.P.D.                                 |
| COLOR glossy 6 mm                  | N.P.D.  | >0,4                         | N.P.D.            | N.P.D.                                 |
| COLOR matte 6 mm                   | N.P.D.  | >0,4                         | N.P.D.            | N.P.D.                                 |
| MARBLE glossy 6 mm                 | N.P.D.  | >0,4                         | N.P.D.            | N.P.D.                                 |
| MARBLE matte 6 mm                  | N.P.D.  | >0,4                         | N.P.D.            | N.P.D.                                 |
| MARBLE velvet 6 mm                 | N.P.D.  | >0,4                         | N.P.D.            | N.P.D.                                 |
| METAL matte 6 mm                   | N.P.D.  | >0,4                         | N.P.D.            | N.P.D.                                 |
| STONE glossy 6 mm                  | N.P.D.  | N.P.D.                       | N.P.D.            | N.P.D.                                 |
| STONE matte 6 mm                   | N.P.D.  | >0,4                         | N.P.D.            | N.P.D.                                 |
| STONE velvet 6 mm                  | N.P.D.  | N.P.D.                       | N.P.D.            | N.P.D.                                 |



FLORIM CERAMICHE S.p.A. a socio unico  
VIA CANALETTO 24 / 41042 FIORANO MODENESE (MO) ITALY  
T. +39 0536 840111 / F. +39 0536 840322  
[www.florim.com](http://www.florim.com)

# CE MARKING

Fine porcelain stoneware SLIM/4  
Coloured body porcelain stoneware SLIM/4  
Fine porcelain stoneware MAGNUM

|  |                      |
|--|----------------------|
|   |                      |
| <b>FLORIM CERAMICHE S.p.A.,</b><br><b>Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia</b>   |                      |
| 09<br>FLORIM 003   |                      |
| <b>EN 14411:2012</b><br>Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$ , for internal and external walls and floorings |                      |
| <b>Reaction to fire</b>  | A1 <sub>FL</sub> /A1 |
| <b>Release of dangerous substances, for:</b>   |                      |
| - Cadmium  | NPD                  |
| - Lead   | NPD                  |
| <b>Breaking strength</b>   | > 700 N              |
| <b>Slipperiness, as:</b>   | See table attached   |
| <b>Tactility</b>   | NPD                  |
| <b>Bond strength/adhesion, for:</b>  |                      |
| Cementitious adhesive, type C2   | NPD                  |
| <b>Thermal shock resistance</b>  | Pass                 |
| <b>Durability, for:</b>  |                      |
| - internal use:  | Pass                 |
| - external use: freeze-thaw resistance   | Pass                 |